



DIMENSIONS IN MILLIMETRES		TITLE	
TOLERANCES UNLESS OTHERWISE STATED		RF & CALIBRATOR PCB	
DIMS TO 2 DEC PLACES ± 0.1	SCREW THREADS	B.A. TO B.S. 93 NORMAL	USED ON
DIMS TO 1 DEC PLACE ± 0.2	UNIFIED TO U.S. 1580	100 METRIC TO B.S. 3603 PT. 12 & 13	QTY/UNIT
DIMS WITHOUT DEC PLACE ± 0.4			
HOLE DIAMETER - 0.15 - 0	THIRD ANGLE PROJECTION		
ANGULAR ± 0°30'			

CHASE ELECTRICS LTD.

2	C/N 90116	26/11/97	7	CN 24128	RB	1/11/97
1	C/N 87050	5.1.89		FACTORY ISSUE		15/6/93
A	FIRST ISSUE	24.7.86	6	SEE CN 93067		7/11/97
No.	DESCRIPTION	CHK'D	APP'D	DATE		
				5	SEE CN 92005	1/11/97
				4	SEE CN 92009	27/82
				3	SEE C.N. 91020	4/3/91

09 0106.01 We 12.11.01
 8 2N 97008 RB 10.1.97

DRAWN	TRACED	CHECKED	APPROVED	DATE	SCALE
PIPCO					

DRAWING No. C1 - 1903 ACTERNA 361 975 S